

Bremsen- und Teilereiniger

Print date 22.01.2024
Revision date 22.01.2024
Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation Bremsen- und Teilereiniger **Unique Formula Identifier** UFI: 9FNK-XE76-E00X-298W

* 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Cleaning of surfaces

1.3 Details of the supplier of the safety data sheet

Supplier

F.W.Klever
Hauptstraße 20
D-84168 Aham
Telephone +49 (0) 8744 96 99 10
Telefax + 49 (0) 8744 96 99 96
E-mail info@ballistol.de
Website www.ballistol.de

Department responsible for information:

Qualitätssicherung

Telephone +49 (0) 8744 96 99 80

E-mail (competent person):

info@ballistol.de

Manufacturer

F.W.Klever
Hauptstraße 20
D-84168 Aham
Telephone +49 (0) 8744 96 99 10
Telefax + 49 (0) 8744 96 99 96
E-mail info@ballistol.de
Website www.ballistol.de

Department responsible for information:

Qualitätssicherung

Telephone +49 (0) 8744 96 99 80

E-mail (competent person): info@ballistol.de

1.4 Emergency telephone number

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

* SECTION 2: Hazards identification

* 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 ICLP1

Classification procedure

Aerosol 1, H222

Aerosol 1, H229

Skin Irrit. 2, H315



Bremsen- und Teilereiniger

Print date 22.01.2024 Revision date 22.01.2024 Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

Classification according to Regulation (EC) No 1272/2008 Classification procedure

[CLP]

Eye Irrit. 2, H319 **STOT SE 3, H336**

Aquatic Chronic 2, H411

Hazard statements for physical hazards

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Hazard statements for health hazards

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Hazard statements for environmental hazards

H411 Toxic to aquatic life with long lasting effects.

* 2.2 Label elements

* Labelling according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms







GHS02

GHS07

GHS09

Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P251 Do not pierce or burn, even after use.

P264 + P265 Wash hands thoroughly after handling. Do not touch eyes.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing and eye protection/face protection.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P332 + P313 If skin irritation occurs: Get medical advice/attention. P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P211 Do not spray on an open flame or other ignition source.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P405 Store locked up.

P501 Dispose of contents / container to recycling

2.3 Other hazards

No data available



Bremsen- und Teilereiniger

Print date 22.01.2024
Revision date 22.01.2024
Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

SECTION 3: Composition / information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

Hazardous ingredients

CAS No	EC No	Index No	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE
64742-49-0	921-024-6	449-328-00-1	Naphtha (Erdöl), mit Wasserstoff behandelt, leicht	35 weight-%	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411	
106-97-8	203-448-7	601-004-00-0	butane	< 30 weight-%	Flam. Gas 1; H220 Press. Gas	
74-98-6	200-827-9	601-003-00-5	propane	< 15 weight-%	Flam. Gas 1; H220 Press. Gas	
64-17-5	200-578-6	603-002-00-5	ethanol	≥ 10 weight-%	Flam. Liq. 2; H225	
REACH No.		Substance	name			
01-2119475514-35		Naphtha (E	Erdöl), mit Wasserstoff beha	ndelt, leicht		

Remark

Aerosol: Propellant propane/butane gas

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

Following inhalation

Provide fresh air.

In the event of symptoms refer for medical treatment.

Following skin contact

After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After eye contact

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Following ingestion

Do NOT induce vomiting. If troubles appear bring to a medical treatment Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

No data available



Bremsen- und Teilereiniger

Print date 22.01.2024
Revision date 22.01.2024
Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Foam Carbon dioxide (CO2) Water spray jet

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide Vapours may form explosive mixtures with air

5.3 Advice for firefighters

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Heating leads to pressure increase and risk of cracking

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Provide adequate ventilation.
Use personal protection equipment.
Remove all sources of ignition.
Do not breath vapour or spray.

6.2 Environmental precautions

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For containment

Take up residues with absorbent material (e.g. sand, sawdust, general-purpose binder).

6.4 Reference to other sections

No data available



Bremsen- und Teilereiniger

Print date 22.01.2024
Revision date 22.01.2024
Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Do not spray on naked flames or any incandescent material.

Keep away from sources of ignition - No smoking.

Protect aerosols from temperatures exceeding 50°C/ 122°F

Do not open with force or incinerate, even when empty

Avoid:

Eye contact

Skin contact

Do not inhale aerosols

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff.

Storing of food in workroom forbidden.

Wash hands before breaks and after work.

Use protective skin cream before handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Materials to avoid

Do not store together with:

Food and feedingstuffs

Further information on storage conditions

Protect from extreme heat and cold.

Keep cool.

7.3 Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No	EC No	Substance name	occupational exposure limit value
64-17-5	200-578-6	Ethanol	Short-term(ml/m³) 1000 (1) (1) 15 minutes reference period (IE)
106-97-8	203-448-7	n-Butane	600 [ml/m³(ppm)] 1450 [mg/m³] Short-term(ml/m³) 750 Short-term(mg/m³) 1810 (UK)
64-17-5	200-578-6	Ethanol	1000 [ml/m³(ppm)] 1920 [mg/m³] (UK)
106-97-8	203-448-7	n-Butane	Short-term(ml/m³) 1000 (1) (1) 15 minutes average value (IE)



Bremsen- und Teilereiniger

Print date 22.01.2024
Revision date 22.01.2024
Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

8.2 Exposure controls

Personal protection equipment

Eye/face protection

With demand: protective glasses

Hand protection

Gloves (solvent-resistant)

Body protection:

Protective clothing

Respiratory protection

Respiratory protection necessary at:

aerosol or mist formation

The following applies to propane in general: If the concentration is exceeded, closed-circuit breathing apparatures must be used

Use filter apparatus type AX, identification colour brown according to EN 371

Environmental exposure controls

Technical measures to prevent exposure

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state

Aerosol

Colour

colourless clear

Odour

fruity

Safety relevant basis data

	Value	Method	Source, Remark
Odour threshold:	not determined		
Melting point/freezing point	not determined		
Boiling point or initial boiling point and boiling range	approx. 80 °C		
flammability	not determined		
Lower and upper explosion limit	Upper explosion limit approx. 15 Vol-%		information concern solvent
Lower and upper explosion limit	Lower explosion limit approx. 3.5 Vol-%		information concern solvent
Flash point	approx. 12 °C		information for solvent
Auto-ignition temperature	approx. 425 °C		Die Daten beziehen sich auf das Lösemittel Ethanol.
Decomposition temperature	not determined		



Bremsen- und Teilereiniger

Print date 22.01.2024
Revision date 22.01.2024
Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

	Value	Method	Source, Remark
рН	not determined		
Viscosity	not determined		
Solubility(ies)	Water solubility		Immiscible
Partition coefficient n- octanol/water (log value)	not determined		
Vapour pressure	approx. 59 hPa (20°C)		The data refer to the solvent
Density and/or relative density	approx. 0.74 g/cm³ (20°C) pressure 1013 mbar		
Relative vapour density	not determined		
particle characteristics	not determined		

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

No data available

10.3 Possibility of hazardous reactions

No data available

10.4 Conditions to avoid

Formation of explosive gas/air mixtures.

Container under pressure. Protect from direct exposure to sunlight and temperatures exceeding 50°C/122°F.

10.5 Incompatible materials

Oxidising agent, strong

10.6 Hazardous decomposition products

No hazardous decomposition products known.

Additional information

Product is stable under normal storage conditions

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity

Animal data

	Effective dose	Method, Evaluation	Source, Remark
Acute oral toxicity	10470 mg/kg Species Rat	OECD 401	Data apply to the main component.
Acute dermal toxicity	not determined		



Bremsen- und Teilereiniger

Print date 22.01.2024
Revision date 22.01.2024
Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

Effective dose Method, Evaluation Source, Remark

Acute inhalation toxicity

124.7 mg/L OECD 403 Data apply to the main component.

Species Rat Exposure time 4 h

Skin corrosion/irritation

not determined

Serious eye damage/irritation

not determined

Sensitisation to the respiratory tract

not determined

Skin sensitisation

not determined

Germ cell mutagenicity

not determined

Carcinogenicity

not determined

Reproductive toxicity

not determined

STOT-single exposure

not determined

STOT-repeated exposure

not determined

Aspiration hazard

not determined

11.2 Information on other hazards

Other information

Frequent persistent contact with the skin may cause skin irritation.

There is no risk in a normal operational application

The product has not been tested. The information is derived from the properties of the individual components.

* SECTION 12: Ecological information

- * 12.1 Toxicity
- * Aquatic toxicity

	Effective dose	Method,Evaluation	Source, Remark
Acute (short-term) fish toxicity	LC50: 8140 g/m3 Species Leuciscus idus (golden orfe) Test duration 48 h		There is no risk in a normal operational application
Chronic (long-term) fish toxicity	not determined		
Acute (short-term) toxicity to crustacea	EC50 9268- 14221 g/m3 Species Daphnia magna (Big water flea) Test duration 48 h		There is no risk in a normal operational application
Chronic (long-term) toxicity to aquatic invertebrate	not determined		



Bremsen- und Teilereiniger

Print date 22.01.2024 Revision date 22.01.2024 Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

	Effective dose	Method, Evaluation	Source, Remark
Acute (short-term) toxicity to algae and cyanobacteria	IC5 5000 g/m3 Species Scenedesmus quadricauda Test duration 7 d		There is no risk in a normal operational application
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
Toxicity to other aquatic plants/organisms	not determined		
Toxicity to microorganisms	not determined		

12

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

No data available

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Additional ecotoxicological information

Additional information

Do not allow uncontrolled discharge of product into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste codes/waste designations according to EWC/AVV

Waste code product Waste name

140603 * other solvents and solvent mixtures

Appropriate disposal / Product

Disposal according to local regulations

Appropriate disposal / Package

Completely emptied packages can be recycled.

Recycle sales packaging via DSD (Duales System Deutschland).

SECTION 14: Transport information

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.1 UN number or ID number	UN 1950	UN 1950	UN 1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable



Bremsen- und Teilereiniger

Print date 22.01.2024
Revision date 22.01.2024
Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA- DGR)
14.3 Transport hazard class(es)	2.1	2.1	2.1
14.4 Packing group	-	-	-
14.5 Environmental hazards	No	No	No

14.6 Special precautions for user

No data available

14.7 Maritime transport in bulk according to IMO instruments

No data available

Land transport (ADR/RID)

UN number or ID number UN 1950 UN proper shipping name AEROSOLS

Transport hazard class(es) 2.1
Hazard label(s) 2.1
Classification code 5F
Packing group Environmental hazards No
Limited quantity (LQ) 1 L

Special provisions 190, 327, 344, 625

Tunnel restriction code D

Sea transport (IMDG)

UN number or ID number UN 1950
UN proper shipping name AEROSOLS

Transport hazard class(es) 2.1
Packing group Environmental hazards No
Limited quantity (LQ) 1 L
Marine pollutant No
EmS F-D, S-U

Air transport (ICAO-TI / IATA-DGR)

UN number or ID number UN 1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es) 2.1
Packing group Environmental hazards No



Bremsen- und Teilereiniger

Print date 22.01.2024 Revision date 22.01.2024 Version 5.1 (en)

replaces version of 20.12.2022 (5.0)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Other regulations (EU)

To follow:

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work

Aerosol directive (75/324/EEC)

15.2 Chemical Safety Assessment

National regulations

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Additional information

National and local regulations concerning chemicals shall be observed.

The information shall be considered in this data accurate and up-to-date knowledge of the revision date. They do not

guarantee the adherence of certain features in the sense of legally binding.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Relevant H- and EUH-phrases (Number and full text)

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

May cause drowsiness or dizziness. H336

H411 Toxic to aquatic life with long lasting effects.

Indication of changes

* Data changed compared with the previous version